

## Polyester Woven Backlit Fabric, PVC Free

### Description

- 100% polyester woven fabric
- Light weight & extremely bright white color on light box & backlit also can be used for exhibition & events, frame display, indoor deco

### Features

- PVC-Free
- Phthalate Free
- Light-Weight

Properties	Test Method	Metric	Imperial
Total Weight	DIN EN ISO 2286-2, ASTM D751	195g/sq.m	5.8 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%Polyester	100%Polyester
Weave Method	N/A	Woven	
Shrinkage	210 °C, 30s	≤2.5%	
Light Transmittance	ANSI PH2.19, ISO 5/2	(41±2) %	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190°C-210°C, 30-90s	
Yellowing Temperature	SUPRKC REX-C400, 30s	≥210°C	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m/100m	55yds/110yds

## Ink Printability

Dye-Sublimation - Transfer , Direct

## Note

It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.