

## Soft Cast, Self Adhesive Vinyl

### Description

Soft cast PVC film

Color: White

Surface: High Glossy

### Release paper

Embossed double PE coated liner, 160gsm

### Application

For vehicle wrapping, trailer, box truck and outdoor signage

Characteristic	Test Method	Average Values
Film Thickness	ISO 4591:1992	50 micron cast PVC film
Adhesive type		Solvent polyacrylate , removable, Light Grey, Repositionable
Dimensional stability	FINAT TM14	Adhered to steel, no shrinkage in cross direction, in length 1mm max.
Temperature resistance		Adhered to aluminum. -20°C to +65°C, no variation
Adhesive power	FINAT TM 1, after 24h, stainless steel	≥ 15N/25mm
Glossiness		≥ 95° (at 60 degree)
Tensile strength	ASTM D882-02; 200MM/MIN	Along: min. 30MPa
		Across: min. 28MPa
Elongation at break	ASTM D882-02; 200MM/MIN	Along: min250%
		Across: min220%
Shelf life		1 year

Storage		Out of direct sunlight at 23°C and 50% humidity
Application temperature		min. +10°C
Durability		Up to 5 years vertical application

### Ink Printability

Compatible with Solvent Ink , Eco-solvent , Latex , and UV Curable Inks

### Attention

After printing the ink must be thoroughly dry in order to avoid any affect on the later combination with the laminate. Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material.

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.