

Woven Backlit Polyester, PVC Free, Good Transparency

Description

- 100% polyester woven fabric with PA coating
- More white & quality, very tight structure
- Perfect with UV inks, also workable with Sol, Eco-sol, Latex

Features

- PVC-Free
- Phthalate Free
- Good Transparency

Properties	Test Method	Metric	Imperial
Total Weight	DIN EN ISO 2286-2, ASTM D751	175g/sq.m	5.2 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	100%polyester
Weave Method	N/A	Woven	
Shrinkage	210 °C, 30s	≤2.5%	
Light Transmittance	ANSI PH2.19, ISO 5/2	(45±2) %	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190°C-210°C, 30-90s	
Yellowing Temperature	SUPRKC REX-C400, 30s	≥210°C	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 505cm	199"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m/100m	55yds/110yds

Ink Printability

Dye-Sublimation Transfer , UV , Solvent , Eco-Solvent , Latex

Note

It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.